

HIGH TENSILE FASTNUTS (INDIA) PVT. LTD.



DIMENSIONAL DETAILS (NYLOCK NUT)

Nyloc Nuts

HTF code----->	NN 4985	NN 5982	NN 5985	NN 6982	NN 6985	NN 8982	NN 10985	NN 1016	NN 1016T
Pitch	0.70	0.80	0.80	1.00	1.00	1.25	1.50	1.50	1.50
A/F	7.00	8.00	8.00	10.00	10.00	13.00	17.00	16.00	16.00
	6.78	7.78	7.78	9.78	9.78	12.73	16.73	15.73	15.73
Nut Height	5.00	6.30	5.00	8.00	6.00	9.50	10.00	8.00	8.00
	4.70	6.00	4.70	7.70	5.70	9.14	9.64	7.64	7.64
Chamfer Dia.	4.60	5.75	5.75	6.75	6.75	8.75	10.80	10.80	10.80
	4.00	5.00	5.00	6.00	6.00	8.00	10.00	10.00	10.00
Washer Dia.	5.90	6.90	6.90	8.90	8.90	11.60	15.60	14.60	14.60
A/C	7.66	8.79	8.79	11.05	11.05	14.38	18.90	17.77	17.77
Wrenching Height	2.20	3.52	2.75	3.92	3.30	5.15	5.50	6.43	6.43

HTF Drwg : Nyloc Nut M6- DIN 985

